

IW-PLV Tower

Pedestal Mass Storage Chassis



Features & Benefits

- Supports 6Gb/s Mini-SAS backplane
- Removable cooling fan module function



Specifications

Standard	EIA-RS310D
M/B Form Factor	ATX(12" x 9.6") , ATX(12" x 10") , EEB(12" x 13")
Dimensions (D x W x H) w/o Front Door	605 x 200 x 430 mm (24" x 17" x 7.8")
Drive Bay	External: Hot-Swap 3.5" x 12 or 2.5" x 12 ; 5.25" x 1 Internal: 2.5" HDD x 2 or 3.5" HDD x 1
Power Supply	Supports PS2 or 2U 1+1 800W Platinum Level CRPS
Indicator	Power Status, HDD, LANs, System Fail Activity LEDs
Front Control Panel	Power Switch, ID Switch, System Reset, NMI, USB 3.0 x 2
Backplane	Mini-SAS (6Gb/s Supported) : SFF 8087 x 3
Cooling Fan	Supports <ul style="list-style-type: none"> ▪ Middle: (92 or 80) x 25 mm PWM Easy-Swap Fan x 3 ▪ Rear: 80 mm x 2 or 120 mm x 1 PWM Fan
Expansion Slot	Full Height PCI Slot x 7
Material	Material: SGCC Thickness: 1.0 mm
Rail Kit	26" Ball-bearing slide rail
Shipping Information	Net Weight: 18.9 kg Gross Weight: 23 kg Container Info <ul style="list-style-type: none"> ▪ Single Packing with pallets: 20': 132pcs, 40': 264pcs, 40'HQ: 264pcs

* The actual product is subject to change without prior notice. In Win Development Inc. reserves the right to make final modifications.

* Above image for reference only. All hardware components are not included.

