



www.in-win.com

# EN Series

SFX 12V V3.21

## Features

- Multiple +12V Output
- Smart Thermal Control to Balance Noise & Cooling
- 80mm Cooling Fan
- MTBF 100KHRs @ 25°C per MIL-STD-217D/F
- Operating Ambient +10°C Minimum to +50°C Maximum
- Meets Intel® Haswell Processors
- ErP Lot 6 Compliant

## Safety



## Dimensions

125(W) X 100(L) X 63.5(H) mm



## Specifications

Model No.	Max. Output	AC Input	PFC	Max. Output Current								
				+12V1	+12V2	+5V	+3.3V	-12V	5VSB	MAX1	MAX2	MAX3
IP-P240EN7-2	240W	100-240V	Active	15A	15A	15A	15A	0.3A	2A	75W	216W	240W
IP-P300EN7-2	300W	100-240V	Active	15A	15A	15A	15A	0.3A	2A	75W	276W	300W

\* MAX1: 5V & 3.3V Total Output

\* MAX2: +12V Total Output

\* MAX3: Total Output Power

## Connectors

Qty.	Model No.					
		24 Pin Main Power Connector	4+4 Pin +12V CPU Power Connector	4 Pin FDD Power Connector	Peripheral Power Connector	SATA Power Connector
	IP-P240EN7-2	1	1	1	1	3
	IP-P300EN7-2	1	1	1	1	3

\* The actual product is subject to change without prior notice. In Win Development Inc. reserves the right to make final modifications.