

IW-RS424-03

4U Storage Rackmount Server



Features & Benefits

- Support SAS 12G / SATA 6G via Expander.
- Tray Less design for 3.5 inch HDD carrier.
- State-of-the-art performance and scalability.
- Supports SES-2 (SCSI Enclosure Service)
- Adjustable Thermal system.
- Tool-less Sliding Rail support.
- CRPS power module support for all series.

Specifications

Standard	EIA-RS310D
M/B Form Factor	ATX (12" x 9.6"); ATX (12" x 10"); EEB (12" x 13")
Dimensions (D x W x H) w/o Front Door	660.4 x 438 x 176 mm (26" x 17" x 7")
Drive Bay	External: Hot Swap 3.5" x 24 Internal: 2.5" HDD x 2 or Rear 2.5" Hot-Swap for OS (SSD 7mm) x 2 (Optional)
Power Supply	Supports <ul style="list-style-type: none"> ▪ Form Factor: Platinum CRPS Redundant ▪ Watt: 800W
Indicator	Power LED, LAN1/LAN2/LAN3/LAN4 LED, System LED, ID LED
Front Control Panel	Power on/off, Reset, NMI, ID SW, USB3.0 x1, Mute button
Backplane	MINI SAS HD /12Gb/s with expander
Cooling Fan	Supports 8038 mm PWM Fan x 3; another 8038 mm Fan for PCI-e (Optional) Modularize design with anti-vibration
Expansion Slot	Full height PCI Slot x 7
SAS 12G Expander support	LSI Expander support
Material	Material: SGCC Thickness: 1.0 mm
Slide Rail	Support 30" screwless slide rail, Ball-bearing

* The actual product is subject to change without prior notice. In Win Development Inc. reserves the right to make final modifications.

* Above image for reference only. All hardware components are not included.



CONTEMPORARY & INNOVATIVE
www.in-win.com