

## IW-RN424-03

4U Dual Node Rackmount Storage Server



### Features & Benefits

- Optimized performance for each node
- Easy maintenance and high availability with two hot-swappable system nodes
- Supports SAS 12G via single expander for each node
- Tray-less design for 3.5-inch HDD carrier
- Compatible with standard form factor motherboard
- Supports tool-less slide rail
- Supports high efficiency CRPS power supplies



### Specifications

<b>Standard</b>	EIA-RS310D
<b>M/B Form Factor</b>	ATX (12" x 9.6"), ATX (12" x 10"), EEB (12" x 13")
<b>Dimensions (D x W x H) w/o Front Door</b>	686 x 482.6 x 176 mm (27" x 19" x 7")
<b>Drive Bay</b>	External: Hot-swap 3.5" x 24 Internal: 2.5" HDD (7mm thickness) x 2 for each node
<b>Power Supply</b>	Supports <ul style="list-style-type: none"> <li>▪ Form Factor: Platinum CRPS redundant with PDB cable management</li> <li>▪ Watt: 1200W</li> </ul>
<b>Front Control Panel / per Node</b>	Button: Power On/Off, NMI, Reset, ID SW Indicator: Power LED, ID LED, System LED, LAN1/LAN2/LAN3/LAN4 LED
<b>Cooling Fan / per Node</b>	<ul style="list-style-type: none"> <li>▪ 6038mm PWM fan x 4</li> <li>▪ Modular design with anti-vibration</li> </ul>
<b>Expansion Slot / per Node</b>	Low-profile PCI slot x 7
<b>Backplane</b>	Mini SAS HD / 12Gb/s with expander
<b>SAS 12G Expander / per Node</b>	Supports LSI 3 x 36R expander
<b>Material</b>	Material: SGCC Thickness: 1.0 mm
<b>Rail Kit</b>	Supports 30" tool-less & ball-bearing slide rail

\* The actual product is subject to change without prior notice. In Win Development Inc. reserves the right to make any final modifications.

\* The above image is for reference only. All hardware components are not included.

