

IW-R200-02N

=Motherboard=

| Brand | Model | CPU Socket | Form Factor |
|------------|------------|-----------------|-------------|
| Supermicro | X10SRL-F | socket-2011 R3 | ATX |
| ASROCKRACK | EP2C612D8A | socket-2011 R3 | ATX |
| Supermicro | H11SSL-NC | Socket-4094 SP3 | ATX |
| Supermicro | X11SAE-F | Socket-1151 | ATX |

=CPU=

| Brand | Model | CPU Socket | TDP |
|--------|-----------------------------------|-----------------|------|
| Intel® | Xeon® Processor E5-2650 v3(2.30G) | Socket-2011 R3 | 105W |
| AMD | EPYC 7451 | Socket-4096 SP3 | 180W |
| Intel® | E3-1280 V6 3.9GHz | Socket-1151 | 72W |

=Hard Disk Drive=

| Brand | Model | Interface | Form Factor | Capacity |
|---------|---------------------|-----------|-------------|----------|
| Seagate | ST3300657SS | SAS | 3.5" | 300GB |
| WD | WD6001FFWX | SATA | 3.5" | 6TB |
| WD | WD2005FBYZ (Golden) | SATA | 3.5" | 2TB |
| Seagate | ST1000DM010 | SATA | 3.5" | 1TB |

=RAID Card=

| Brand | Model | Ports | Data Rates |
|-------|---------|--------------|-------------|
| LSI | 9271-8i | Internal x 8 | SATA/SAS 6G |

=Heatsink=

| Brand | Model | Form Factor | TDP |
|----------|-------------|-------------|------|
| Dynatron | A26 | Socket-4096 | 180W |
| Dynatron | K650 | Socket-1151 | 95W |
| Dynatron | R14(Narrow) | Socket-2011 | 150W |

=Power Supply=

| Brand | Model | Form Factor | Wattage |
|--------|---------------|--------------|-----------|
| In-Win | PS2-S500BT7-3 | PS2 | 500W |
| Zippy | M1P2-5500V4V | 2U Redundant | 500W(1+1) |

Note:

* The listed components had been tested by In Win lab according to In Win's verification standard.

* To avoid failure and errors, please also reference components vendors' user manual.

* The actual performance is affected by host's hardware specification, software, file system, and other conditions.