


IW-RS208-02SN

2U Storage Rackmount Server Chassis



Features & Benefits

- 2U rack-mount short depth chassis
- Single or redundant gold level high-efficiency power supply
- SAS (SGPIO) and SATA 6Gb supported
- Easy-swap 80 mm PWM fans with Anti-Vibration mechanism
- External 3.5" or 2.5" x 8 hot-swap HDD trays with lock supported



Specifications

Standard	EIA-RS310D
M/B Form Factor	ATX (12" x 9.6"), CEB (12" x 10.5")
Dimensions (D x W x H) w/o Front Door	571.5 x 482.6 x 87 mm (22.5" x 19" x 3.5")
Drive Bay	External: Hot-Swap 3.5" x 8 or 2.5" x 8, Slim ODD x 1 Internal: 2.5" HDD x 2, 3.5" HDD x 1 (Optional)
Power Supply	Supports <ul style="list-style-type: none"> ▪ Form Factor: Single or 1+1 Redundant ▪ Watt: Single 500W, Redundant 550W
Indicator	Power Status, HDD, LANs, System Fail Activity LEDs
Front Control Panel	Power Switch, ID Switch, System Reset, NMI, USB 3.0 x 2
Backplane	<ul style="list-style-type: none"> ▪ SATA (6Gb/s Supported) ▪ Mini-SAS (6Gb/s Supported) ▪ Mini-SAS HD (12Gb/s Supported)
Chassis Security	Intrusion Switch (Optional)
Cooling Fan	Supports 80 x 25 mm / 80 x 38 mm PWM Easy-Swap Fan x 3
Expansion Slot	Low Profile PCI Slot x 7
Material	Material: SGCC Thickness: 1.0 mm
Rail Kit	Support 28" screwless slide rail, Ball-bearing
Packaging Dimensions (D x W x H)	742 x 577 x 212 mm
Shipping Information	Net Weight: 10.7 kg Gross Weight: 16.5 kg Container Info <ul style="list-style-type: none"> ▪ Single Packing with pallets: 20': 176pcs, 40': 384pcs, 40'H: 432pcs

* The actual product is subject to change without prior notice. In Win Development Inc. reserves the right to make final modifications.

* Above image for reference only. All hardware components are not included.



CONTEMPORARY & INNOVATIVE
www.in-win.com