

IW-RS208-04

2U Rackmount Storage Server



Features & Benefits

- Supports SAS 12G / SATA 6G via expander
- Tool-less design for 3.5-inch HDD carrier
- Designed for performance and scalability
- Supports SES-2 (SCSI Enclosure Service)
- Specialized flexible cooling design
- Supports tool-less sliding rail
- Supports high efficiency CRPS power supplies

Specifications

Standard	EIA-RS310D
M/B Form Factor	ATX (12" x 9.6"), ATX (12" x 10"), EEB (12" x 13")
Dimensions (D x W x H) w/o Front Door	660.4 x 482.6 x 87 mm (26" x 19" x 3.5")
Drive Bay	External: Hot-swap 3.5" x 8 Internal: 2.5" x 2 or rear hot-swap 2.5" (7mm SSD) x 2 for OS (Optional)
Power Supply	Supports <ul style="list-style-type: none"> ▪ Form Factor: Platinum CRPS redundant ▪ Watt: 800W
Indicator	Power LED, LAN1/LAN2/LAN3/LAN4 LED, System LED, ID LED
Front Control Panel	Power On/Off, Reset, NMI, ID SW, USB 3.0 x 1, Mute Button
Backplane	Mini SAS HD /12Gb/s without expander
Cooling Fan	<ul style="list-style-type: none"> ▪ 8038mm PWM fan x 3, 4028mm fan x 2 ▪ Modular design with anti-vibration
Expansion Slot	Low-profile PCI slot x 7
Material	Material: SGCC Thickness: 1.0 mm
Rail Kit	Supports 20" or 28" tool-less & ball-bearing slide rail

* The actual product is subject to change without prior notice. In Win Development Inc. reserves the right to make any final modifications.

* The above image is for reference only. All hardware components are not included.

